

REQUEST

Bill of quantities for
the required substrate preparation works for
all Plastifloor® floor coating systems

Page 1

| <u>Pos.</u> | <u>Quantity</u> | <u>Unit</u> | <u>Article/work</u> | <u>Unit price EUR</u> | <u>Total EUR</u> |
|-------------|-----------------|----------------|---|-----------------------|------------------|
| 1. | | | Substrate preparation | | |
| 1.01 | | m ² | Traverse the surface crosswise With medium speed with Blastrac- shot-blasting machine 1-8 D, or star lamella milling machine e.g.: FR 300 as required. | | |
| | | | Prepare lateral faces manually for The coating by using an angle grinder. | _____ , _____ | _____ , _____ |
| 1.02 | | m | Remove fillings of expansion Joints in the surface. | | |
| | | | Cut open cracks in the surface. | | |
| | | | Billing according to measurement. | _____ , _____ | _____ , _____ |
| 1.03 | | m ² | Vacuuming of surface with vacuum cleaner for thorough cleaning. | _____ , _____ | _____ , _____ |
| 1.04 | | m | Cut in angular connections to inspection pits, inlets, canals or machines. Deepen the connection so that flank adhesion to the edge is being strengthened. | | |
| | | | Billing according to measurement. | _____ , _____ | _____ , _____ |

transfer:

_____ , _____