

Enquiry

**Bill of Quantities for
Plastistone® sprinkle coat
for industrial floors (4 - 6 mm)**

Pos.	Unit	Article / Description	Individual Price	Total Price
		floor preparation		
1.01	m ²	mill surface with steel-ball blast plant 1-8 D, or with normal speed		
		preparing edges with an angle grinder by hand	_____ , ____	_____ , ____
1.02	m	open cracks closed with filler by using tools		
		invoive concerning measurement	_____ , ____	_____ , ____
1.03	m ²	hooving the surface with a vacuum cleaner		
			_____ , ____	_____ , ____
1.04	m	open joints to shaft, to inlets, canal or machine by using tools, the strengthened recessed joint realizes a better bond at the edge of the coat		
		invoicing concerning measurement	_____ , ____	_____ , ____
		total:		_____ , ____

Pos.	Amount	Unit	Article / Description	Individual Price	Total Price
				last page: _____ , ____	
2.01		m ²	Plastifloor® - coating precoating of the prepared floor to close pores material: Plastistone® T 19-36 material used: 0,5 kg/m ² per level until the pores are closed dusting with 0,2 – 0,7 mm quartz sand	_____ , ____	_____ , ____
2.02		kg / h	<u>contingency</u> equalization deep or large holes, swales and cracks in the floor will be removed in advance, this happens by order of the owner concerning the record of wages and costs of material working hour: mortar based on resin: an even (corresponding to DIN 18202) coat can only be produced, if there is the necessary ground available or can be processed by order of the owner	_____ , ____	_____ , ____
2.03		kg/h	If there are no slopes (approx. 2 %), they can be processed from mortar based on resin by order of the owner concerning the record of wages and costs of material. If the coat is processed without slopes formation of puddles is possible. 1 kg mortar based on resin T 19-36: 1h working time:	_____ , ____	_____ , ____
2.04		m	grouting of expansion joints with acrylate resin size of the joints: material: Plastistone® M 670	_____ , ____	_____ , ____

Pos.	Amount	Unit	Article / Description	Individual Price	Total Price
2.05		m ²	<p>troweling of Plastistone[®] litter coat</p> <p>thickness of the layer: 4 - 6 mm</p> <p>material used: 3,0 kg resin mixture T 19-36 10 kg decorative filler</p> <p>skid-proof (class): R12</p> <p>there are variations concerning colour and mixture possible, but they do not result in claims of warranty</p> <p>producer: Plasti-Chemie GmbH Klopstockstr. 19 D 08525 Plauen</p> <p>----- phone: 0049 3741 55830 fax: 0049 3741 558327</p>	last page: _____ , ____	_____ , ____
2.06		m ²	<p>sealing of the coated floor</p> <p>material: Plastistone[®] 19-38</p> <p>material used: 0,4 kg</p> <p>site installations</p>	_____ , ____	_____ , ____
3.01			<ul style="list-style-type: none"> - installation of the site, tools and machines stay at the site during the construction period - CM-measuring and taking minutes - 1 pull-off measuring and taking minutes - disposal of empty boxes or pails - transport to and from the site (once) - allowance for the personnel 	_____ , ____	_____ , ____

Pos.	Unit	Article / Description	Individual Price	Total Price
			last page:	_____ , ____
		<u>summary</u>		
		preparation of the floor		
		Plastifloor® coating		
		installation of the site		_____ , ____
		net price		
		VAT	_____ %	_____ , ____ _____
		total		_____ , ____