

Enquiry

Bill of Quantities for
Plastistone® Terrazzo
for normal load (8 – 10 mm)

Pos.	Unit	Article / Description	Individual Price	Total Price
		floor preparation		
1.01	m ²	mill surface with steel-ball blast plant 1-8 D, or with normal speed		
		preparing edges with an angle grinder by hand	_____ , ____	_____ , ____
1.02	m	open cracks closed with filler by using tools		
		invoice concerning measurement	_____ , ____	_____ , ____
1.03	m ²	hooving the surface with a vacuum cleaner	_____ , ____	_____ , ____
1.04	m	open joints to shaft, to inlets, canal or machine using tools, the strengthened recessed joint realizes a better bond at the edge of the coat		
		invoicing concerning measurement	_____ , ____	_____ , ____
		total:		_____ , ____

Pos.	Amount	Unit	Article / Description	Individual Price	Total Price
				last page: _____ , ____	
2.01		m ²	Plastistone® - coating precoating of the prepared floor to close pores material: Plastistone® 19-36 material used: 0,4 kg/m ² per level until the pores are closed dusting with 0,2 – 0,7 mm quartz sand	_____ , ____	_____ , ____
2.02		kg / h	<u>contingency</u> equalization deep or large holes, swales and cracks in the floor will be removed in advance, this happens by order of the owner concerning the record of wages and costs of material working hour: mortar based on resin: an even (corresponding to DIN 18202) coat can only be produced, if there is the necessary ground available or can be processed by order of the owner	_____ , ____	_____ , ____
2.03		m	grouting of expansion joints with acrylate resin and installing of Terrazzo joint profiles size of the joints: product: to name by supplier	_____ , ____	_____ , ____
2.04		m ²	spreading of Plastistone® Terrazzo and screeding with a smoothing trowel		_____
			total:		_____ , ____

Pos.	Amount	Unit	Article / Description	Individual Price	Total Price
------	--------	------	-----------------------	------------------	-------------

last page: _____ , ____

thickness of the layer: 10 mm
 material used: 6 kg resin Plastistone
 Terrazzo
 19,5 kg filler , Terrazzo
 grit mixture
 5,4 kg decorative filler

color for resin and grit mixture as requested
 no:

there are variations concerning color and
 mixture possible, but they do not result in
 claims of warranty

producer: Plasti-Chemie GmbH
 Klopstockstr. 19
 D 08525 Plauen

_____ , ____ _____ , ____

 phone: 0049 3741 55830
 fax: 0049 3741 558327

2.05	m ²	tough polish of Terrazzo-surface after 12 to 14 curing hours, filling wholes with Plastistone Terrazzo resin		
------	----------------	--	--	--

2.06		finishing polish of Terrazzo-surface after further 12 to 14 hours after filling		
		skid-proof class: R 11		

2.07	m ²	Final treatment of the surface by using wax		
		material: to name by supplier		
		site installations	_____ , ____	_____ , ____

3.01		- installation of the site, tools and machines stay at the site during the construction period		
		- CM-measuring and taking minutes		
		- 1 pull-off measuring and taking minutes		
		- disposal of empty boxes or pails		
		- transport to and from the site (once)		
		- allowance for the personnel	_____ , ____	_____ , ____

Pos.	Unit	Article / Description	Individual Price	Total Price
			last page:	_____ , ____
		<u>summary</u>		
		preparation of the floor		
		Plastistone® coating		
		installation of the site		
		net price		_____ , ____
		VAT	_____ %	_____ , ____
		total		_____ , ____